



GRANGE WORKS, GRANGE ROAD
BATLEY, WEST YORKSHIRE, WF17 6LN



WWW.RELIANTRUBBER.CO.UK



01924 420098



INFO@RELIANTRUBBER.CO.UK



NR/SBR COMMERCIAL RUBBER



NR/SBR Commercial Rubber Sheetting is a blend of Natural Rubber and synthetic SBR (Styrene-Butadiene Rubber) and displays the positive characteristics of both, making it an excellent all-rounder for a wide range of environments and applications.


It has an excellent resistance to water and ozone, along with an average resistance to acids. The rubber's good tensile strength and abrasion resistance make it ideal for the manufacture of skirts, gaskets, seals, and sleeves.



FULL ROLLS



CUT TO LENGHTS



BESPOKE GASKET

For additional details,
please scan the QR
code, which will direct
you straight to our
website.





RELIANT RUBBER 

@RELIANTRUBBER 

RELIANT RUBBER 

RELIANT RUBBER ENGINEERS LIMITED 

NR/SBR COMMERCIAL RUBBER

FULL ROLL DIMENSIONS	10M LONG X 1.2M WIDE OR 5M LONG X 1.2M WIDE	ONLY 15MM THICK ROLLS ARE 5M LONG
GRADE	COMMERCIAL	
COLOUR	BLACK	
SURFACE FINISH	SMOOTH/SMOOTH	
HARDNESS, SHORE A	65+/-5	ISO 7619-1
ABRASION RESISTANCE	AVERAGE	
ELONGATION AT BREAK %	200	ISO 37
TENSILE STRENGTH	2.5-3MPA	
TEMPERATURE RANGE	-20 TO +70 C	

CHEMICAL RESISTANCE

WATER	OZONE	ACIDS	SOLVENTS	OILS	EXCELLENT
					ABOVE AVERAGE
					AVERAGE
					BELOW AVERAGE
					POOR