



GRANGE WORKS, GRANGE ROAD
BATLEY, WEST YORKSHIRE, WF17 6LN



WWW.RELIANTRUBBER.CO.UK



01924 420098



INFO@RELIANTRUBBER.CO.UK



CR NEOPRENE



Neoprene Rubber sheeting is a synthetic rubber widely used in outdoor applications due to its excellent resistance to weathering, ozone, and ageing.


It has a good resistance to high temperatures and does not soften under extreme exposure like Natural Rubber. It can be compounded to make it flame retardant and is available in both a solid rubber and an expanded foam.



FULL ROLLS



CUT TO LENGTHS



BESPOKE GASKET

For additional details, please scan the QR code, which will direct you straight to our website.





RELIANT RUBBER 

@RELIANTRUBBER 

RELIANT RUBBER 

RELIANT RUBBER ENGINEERS LIMITED 

CR NEOPRENE

FULL ROLL DIMENSIONS	10M LONG X 1.4M WIDE	
GRADE	COMMERCIAL	
COLOUR	BLACK	
SURFACE FINISH	SMOOTH/SMOOTH	
HARDNESS, SHORE A	70+/-5	ISO 7619-1
ABRASION RESISTANCE	AVERAGE	
ELONGATION AT BREAK %	200	ISO 37
TENSILE STRENGTH	4MPA	
TEMPERATURE RANGE	-30 TO +70 C	

CHEMICAL RESISTANCE

WATER	OZONE	ACIDS	SOLVENTS	OILS	EXCELLENT
					ABOVE AVERAGE
					AVERAGE
					BELOW AVERAGE
					POOR